MINERALS WEDG Responsibly

IIII

We have expertise in extracting, shipping, and delivering mineral products with high efficiency.





About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium-grade minerals that cater to the specific requirements of our valued customers.



"DELIVERING EXCELLENCE AND RELIABILITY IN MINERAL SUPPLY FOR INDUSTRIAL AND DIVERSE APPLICATIONS"

Whether you need minerals for industrial applications or various other purposes, we are dedicated to delivering exceptional quality and reliability. Our reliable supply chain ensures prompt and efficient delivery, while our customer service goes above and beyond to ensure your satisfaction. As your trusted partner, we provide seamless collaboration, offering customized solutions and expert guidance. When you choose us as your mineral supplier, you can expect superior quality, reliability, and a commitment to meeting your unique needs. Experience the difference of working with a top-tier mineral supplier in the USA.

OUR PRODUCTION SITE

LOCATED IN CHEMIDTHI, AP, INDIA

MMI India mining site is located in Chemidthi, Andhra Pradesh where our primary extraction site is located. We are continuously expanding our footprint by acquiring more land with expanded production offering. Our shipping port is Krishnapatman which is located about 55 kilometers from the mining site. We also have refining capability working with local refiners to meet the specification of our customers. MMI has state of the art earth moving equipment and we continue to increase our mining capacity by investing in state-of-the-art technology.



OUR PRODUCTS



QUARTZ

Quartz is a chemical compound consisting of one part silicon and two parts oxygen (silicon dioxide SiO2). It is one of the most useful natural material that is resistant to chemicals and heat.



VERMICULITE

Vermiculite comprises a group of hydrated, laminar magnesium-aluminu-iron silicate minerals resembling mica. Vermiculite's water-wicking, lightweight, and thermal-resistant properties make it ideal for a variety of applications and products across an array of industries.



Our in-house manufacturing facility processes synthetic rutile through the upgrading of ilmenite ore to remove impurities and yield a feedstock for production of titanium tetrachloride through the chloride process.



Our in-house manufacturing facility processes of garnet sand in different mesh sizes as per our customer's needs. We have access to abundant natural resources of garnet sand to supply to our customers worldwide.



Bauxite is a naturally occurring mineral rich in aluminum oxides and hydroxides. It's the primary source for aluminum production and is prized for its high alumina content.



Mica is a mineral name given to a group of minerals that are physically and chemically similar. Micas are fairly light and relatively soft, and the sheets and flakes of mica are flexible. Mica is heat-resistant and does not conduct electricity.



Feldspar comprises of different minerals like potassium, aluminum, calcium and silicates. It is one of the most important ingredients in all types of ceramic bodies and glaze. It is used in Glass and ceramic industries.



Our in-house fabrication facility can machine washed china clay into powdered form to suit your specification, print, or requirement. We have abundant product supply for the high-quality Kaolin (china clay) to worldwide market.



Naturally occurring mineral with hardness and heat resistance, derived from bauxite through refining processes, serves as a vital precursor for aluminum production.



Pleochroic aluminum silicate mineral valued for refractory applications and occasionally used as a unique gemstone in jewelry.



Dense mineral essential in drilling, medical imaging, coatings, and industry for its weight and properties, commonly found in sedimentary deposits worldwide.



Highly plastic and fine-grained clay used in ceramics for its molding and firing properties, crucial in porcelain and fine china production.



Titanium iron oxide mineral valued for its titanium content, used in pigments, aerospace, manufacturing, and as a source of titanium dioxide.



It serves as a crucial component in refractories, construction materials, ceramics, and more, thanks to its heat resistance, electrical insulation, and pH-regulating abilities.



MULLITE

High-temperature ceramic material prized for its excellent thermal stability, mechanical strength, and resistance to thermal shock in diverse industrial applications.



SILICA SAND

Naturally occurring granular material used in various industries, including glassmaking, construction, foundry work, and manufacturing of silicon chips.



High-temperature aluminum silicate mineral valued for its heat resistance, excellent thermal stability, and versatility in refractory applications and ceramics.



Naturally occurring mineral used in ceramics, refractories, foundries, and electronics for its heat-resistant, high-density characteristics and its role as a source of zirconium.



nartz

Quartz, a mineral composed of silicon dioxide (SiO2), is highly versatile and finds applications in various industries due to its unique properties

MMI Quartz Applications

8

ELECTRONICS AND SEMICONDUCTORS:

GLASS AND

Quartz is a key component in the production of quartz crystals and oscillators used in electronic devices like watches, clocks, radios, and microprocessors. Its piezoelectric properties make it valuable for precise timekeeping and frequency control.

High-purity quartz is used in the manufacture of optical lenses, windows, **OPTICAL LENSES** and prisms due to its transparency and ability to transmit ultraviolet (UV) light. It is also a key component in the production of high-quality glass products, including camera lenses and telescope mirrors.

QUARTZ Engineered quartz countertops, also known as quartzite or quartz COUNTERTOPS surface, are popular in kitchens and bathrooms due to their durability, stain resistance, and attractive appearance.

CONSTRUCTION Quartz is used in the production of concrete, mortars, and other construction materials, where its hardness and durability enhance the AND BUILDING MATERIALS strength of the final product.

Quartz is used as a filler and flux in the manufacture of ceramics, CERAMICS AND PORCELAIN including tiles, sanitaryware, and porcelain products.

WATER FILTRATION Quartz sand is commonly used in water filtration systems to remove impurities and sediments from drinking water and industrial processes.

High-purity quartz glass is used to make laboratory equipment like beakers LABORATORY test tubes, and crucibles due to its resistance to high temperatures and GLASSWARE chemical corrosion.

Solar cells often use quartz as a substrate due to its transparency and

durability, enabling the efficient capture of sunlight for electricity generation.

SOLAR PANELS

- Product Typical Characteristics

- Luste
- Transmitting UV Light
- Heat Resistance
- **Electrical Insulation**

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and Our state-of-the-art more. facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us ____

(855)208-2224

info@mallimineralsinternational.com





QUARTZ LUMP

QUARTZ POWDER

MATERIAL	FORM	SIZE
QUARTZ	CRUDE	1 FEET
QUARTZ	LUMPS	4 cm - 12 cm
QUARTZ	POWDER	#200, 240, 300, 325 MESH

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT
Color:	White
Density:	2.65 to 2.75 g/cm ³
Melting Point:	1,650° celsius
Mohs hardness:	7

PARAMETERS	GRADE A	GRADE B
SiO2	99.95%	98.0-99.5%
Al ₂ O ₃	0.02%	< 0.5%
Fe ₂ O ₃	0.01%	< 0.1%
Na ₂ O	0.02%	< 0.2%
K ₂ O	0.03%	< 0.2%
CaO	0.04%	< 0.1%
MgO	0.05%	< 0.2%
TiO ₂	0.01%	< 0.02%
LOI	0.02%	0.09%
E.C	3.4	< 13



ica

Mica is a versatile mineral with several applications across various industries due to its unique properties, including heat resistance, electrical insulation, and flexibility.

MMI MICA Applications

.

Mica is used as an insulating material in electrical and electronic equipment, ELECTRICAL INSULATION such as capacitors, transformers, and electrical wiring, due to its excellent electrical insulating properties. Mica is a common ingredient in cosmetics, where it adds a shimmering COSMETICS AND or glittery effect to products like eyeshadows, lipsticks, and nail polishes. PERSONAL CARE

PAINTS AND Mica is used in paints, coatings, and automotive finishes to enhance their durability, texture, and resistance to weathering. COATINGS

CONSTRUCTION Mica is added to construction materials like plaster, stucco, and concrete MATERIALS to improve their workability and resistance to cracking.

OIL WELL In the oil and gas industry, mica is used as a drilling mud additive to control fluid loss and lubricate drilling equipment. DRILLING

PLASTICS AND Mica is used as a filler and reinforcement material in plastics and rubber products to enhance their thermal and mechanical properties. RUBBER

Due to its ability to withstand high temperatures, mica is used as a heat HEAT INSULATION shield and insulation material in appliances, ovens, and furnaces.

FIREPROOFING Mica is added to fire-resistant materials to improve their fireproofing properties.

Mica can be used as a dry lubricant in certain applications where oil-based LUBRICANTS lubricants are not suitable.

Mica is sometimes used in agriculture as a soil conditioner to improve AGRICULTURE aeration and water retention in the soil.

Product Typical Characteristics

- Floxibility
- Heat Resistance

- Lightweight
- Color Range

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us ____

(855)208-2224

info@mallimineralsinternational.com



NATUREAL MICA



MICA SCRAP





MICA FLAKES

MICA POWDER

MATERIAL	FORM	GRADE
NATUREAL MICA	CRUDE	150-200 MM
MICA SCRAP	SCRAP	100 - 150 MM
MICA FLAKES	FLAKES	10 - 100 MM
MICA POWDER	POWDER	#200
MICA SHEETS	SHEET	ALL SIZES

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT
Color	green, brown, black
Density	2.7 to 3.0 g/cm ³
Melting Point	1,090 to 1,370° celsius
Mohs hardness	25-4

PARAMETERS	PERCENTAGE VALUE
SiO ₂	48.24%
Al ₂ O ₃	32.61%
Na ₂ O	0.86%
к <u>,</u> о	9.10%
Fe ₂ O ₃	2.75%
Moisture	0.20%
Loss on Ignition	4.6%

Vermiculite Mineral

We have expertise in extracting, shipping, and delivering mineral products with high efficiency.

MMI Vermiculite Applications

Vermiculite has excellent insulating properties due to its ability to trap air within its expanded layers. It is commonly used as insulation in construction materials, such as loose-fill insulation, concrete aggregates, and insulation boards.

- **HORTICULTURE** & GARDENING Vermiculite is widely used in gardening and horticulture. It improves soil aeration, moisture retention, and nutrient availability. It can be added to potting mixes or used as a standalone soil amendment to promote healthy plant growth.
- FIREPROOFING Expanded vermiculite has high resistance to heat and fire. It is used in fireproofing materials, such as sprays and coatings, to provide a protective barrier against flames and heat transfer.

LICHTWEICHT CONCRETE Vermiculite is often used as an aggregate in lightweight concrete, also known as vermiculite concrete. The resulting material is lightweight, insulating, and has good fire resistance, making it suitable for construction applications.

PACKAGING Expanded vermiculite is used as a packaging material for fragile and sensitive goods. Its lightweight and cushioning properties help protect items during transportation.

VERMICULITE Vermiculite boards are manufactured using vermiculite and other BOARDS & PANELS binders. These boards have excellent thermal properties and are used in applications such as wood stoves, fireplaces, and thermal insulation boards.

INDUSTRIAL Vermiculite finds various industrial applications, including filtration, APPLICATIONS absorbents, friction linings, sealants, and coatings.

Product Typical Characteristics

INSULATION

- Lightweight
- Fire Resistance
- Intermatinsulation
 Sound Absorption
- Sound Absorption
- Aeration and Water Retention
- Chemical Stability
- Expansion Ability
- Incombustibility
 Non-Asbestos
- Chamical Inarte
- Color and Texture
- Abrasive Properties

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us

(855)208-2224

info@mallimineralsinternational.com





FINE GRADE





MEDIUM GRADE

SUPER FINE GRADE

LARGE GRADE



EXTRA LARGE GRADE



RAW VERMICULITE

MATERIAL	FORM	GRADE
RAW VERMICULITE	CRUDE	RAW
SUPER FINE GRADE	0.5 TO 1 MM	EX-FOLIATED
FINE GRADE	1 TO 2 MM	EX-FOLIATED
MEDIUM GRADE	2 TO 4 MM	EX-FOLIATED
LARGE GRADE	4 TO 8 MM	EX-FOLIATED
EXTRA LARGE GRADE	8 TO 12 MM	EX-FOLIATED

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT
Moisture content	2 %
Apparent weight	0.25-0.35 g/cc
рН	6-9
Sintering temperature	Approx. 1200 °C
Melting point	Approx. 1330 °C

PARAMETERS	PERCE	NT/	GE VALUE
SiO ₂	35%	.	41%
Al ₂ O ₃	6%	-	9.5%
Fe ₂ O ₃	6%	-	9.5%
MgO	21.5 %	-	25.5 %
CaO	2%	28	6%
K ₂ O	3%	-	6%
TiO ₂	0.6%	-	1.4 %
P203	0.2%	-	2%



Feldspar

Feldspar comprises of different minerals like potassium, aluminum, calcium and silicates. It is one of the most important ingredients in all types of ceramic bodies and glaze.

MMI Feldspar Applications

.

CERAMICS AND GLASS	Feldspar is a vital ingredient in the production of ceramics and glass, where it acts as a flux, reducing the melting temperature and improving the overall structure and properties of the materials.
CONSTRUCTION MATERIALS	It is used in the manufacturing of tiles, plumbing fixtures, and other construction materials to enhance their durability and appearance.
PAINT AND COATINGS	Feldspar is added to paint and coatings to improve their adhesion, consistency, and resistance to abrasion and weathering.
FILLERS AND EXTENDERS	It serves as a filler and extender in products like adhesives, sealants, and plastics, improving their strength and workability.
ABRASIVES	Feldspar's hardness makes it suitable for use in the production of abrasives like grinding wheels and sandpapers.
CHEMICAL INDUSTRY	It is used in various chemical processes and as a flux in metallurgical applications.
OIL AND GAS DRILLING	Feldspar is added to drilling fluids to enhance their viscosity and reduce friction during drilling operations.
CERAMIC GLAZES	In the ceramics industry, it is used in glazes to enhance their color, texture, and durability.
ELECTRONICS	Some specialized types of feldspar are used in the manufacturing of electronic components such as capacitors and insulators.

Product Typical Characteristics

www.mallimineralsinternational.com

- Mineral Group
- Color and Varieties

- Purity and Impurities
 - Melting Point
 - Thermal Stability
- Particle Size and Grain Distribution
 Electrical Properties

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us

(855)208-2224

info@mallimineralsinternational.com





SODIUM FELDSPAR LUMPS

POTASIUM FELDSPAR LUMPS





SODIUM FELDSPAR POWDER

POTASSIUM FELDSPAR POWDER

MATERIAL	FORM	SIZE
SODIUM FELDSPAR	LUMPS	10 - 300 MM
SODIUM FELDSPAR	POWDER	#200, 325 MESH
POTASIUM FELDSPAR	LUMPS	10 - 300 MM
POTASIUM FELDSPAR	POWDER	#200, 325 MESH

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT
Moisture content	2 %
Apparent weight	0.25-0.35 g/cc
рН	6-9
Sintering temperature	Approx. 1200 °C
Melting point	Approx. 1330 °C

POTASSIUM FELDSPAR CHEMICAL ANALYSIS

PARAMETERS	PERCENTAGE VALUE
K ₂ O	11.20%
Na ₂ O	2.50%
Fe ₂ O ₃	0.10%

SODIUM FELDSPAR CHEMICAL ANALYSIS

PARAMETERS	PERCENTAGE VALUE
SiO ₂	67.36%
Al ₂ O ₃	19.46%
Fe ₂ O ₃	0.40%
MgO	0.50 %
CaO	0.70%
к20	0.31%
TiO ₂	0.05%
NA,O	0.05%



Rutile Sand Mineral

Rutile, sand is a mineral composed primarily of titanium dioxide (TiO2) and is valued for its high titanium content. It is used in various applications across industries.-

MMI Rutile Sand Applications

.

 PRODUCTION
 plasti

 WELDING
 It's us

 ELECTRODES
 th of v

 CERAMICS
 In cer

 ENHANCEMENT
 result

 METAL ALLOYS
 Rutile

 PLASTICS
 It's us

 MODIFICATION
 UV result

PIGMENT

CASTING

Rutile sand is crucial for producing high-quality paints, coatings, and plastics due to its brightening and opacifying properties.

It's used as a coating for welding rods, improving the quality and strength of welded joints, especially in high-temperature applications.

In ceramics manufacturing, rutile sand enhances firing characteristics, resulting in stronger and more durable products.

IETAL ALLOYS Rutile sand provides titanium for aerospace and industrial alloys, ensuring high strength and corrosion resistance.

ASTICS It's used as a filler in plastics to enhance thermal stability, strength, and UV resistance, crucial in many plastic applications.

ELECTRODES AND Rutile sand serves as an electrode material and a source of titanium in electrochemical processes.

REFRACTORY It improves the thermal shock resistance of refractory materials, making MATERIALS them suitable for high-temperature applications like furnaces and kilns.

> Rutile sand is employed as a mold and core material in casting processes due to its ability to withstand high temperatures and maintain mold integrity.

WATER TREATMENT Rutile-based products assist in removing impurities from water in various purification processes.

Product Typical Characteristics

- Mineral Structure
- Color and Appearance
- Particle Size and Distribution
- Density
- Titanium Dioxide Content
- Impurities
- Melting Point
- Heat Resistance
- Chemical Reactivity
- Applications and Uses
- Environmental Impact

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium arade minerals that cater to the specific requirements of our valued customers.

Contact Us ____

(855)208-2224

info@mallimineralsinternational.com





RUTILE SAND

RUTILE SAND POWDER



SYNTHETIC RUTILE SAND

MATERIAL	FORM	GRADE	
RUTILE	SAND	#200, #300, #325	
RUTILE	SAND	R87, R90, R92, R95	
SYNTHETIC RUTILE	SAND	SR87, SR90, SR92, SR95	

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT	PARTICULARS	GRADEI	GRADE II
Color:	red, brown, and black	TiO2	92%	90%
Density:	4.2 to 4.3 g/cm³	Specific Gravity	4.2 - 4.25	4.2 - 4.25
Melting Point:	1,830 °C	Bulk Density (Kg/m³)	2630-2650	2630-2650
Mohs hardness:	6-6.5			

(Mesh) ASTM	Sieve opeing in Microns	%	%
40	425	0.02	0.02
60	250	7.72	8.08
80	180	24.48	24.08
100	150	22.39	21.94
120	125	27.7	27.81
140	106	13.22	13.59
170	90	3.15	3.15
(-) 170	(-) 90	126	1.29
Sieve loss	Sieve loss	0.06%	0.04%



Our in-house fabrication facility can machine washed china clay into powdered form to suit your specification, print, or requirement. We have abundant product supply for the high-quality Kaolin (china clay) to worldwide market.

٠		•	•	MMI Kaolin
٠	•	•	•	
•		•	•	Applications

1.50		12	10	23		
•	•		٠	٠	•	
				•		

Kaolin is used as a filler and coating pigment in the paper industry to PAPER INDUSTRY improve printability, brightness, and smoothness of paper products. It is a key ingredient in the production of ceramics and pottery, enhan-CERAMICS AND cing their strength, whiteness, and workability. POTTERY

.

Kaolin is used as a pigment in paints and coatings to control gloss, PAINTS AND COATINGS improve opacity, and provide a smooth finish.

In the plastics industry, kaolin is used as a filler and reinforcement agent PLASTICS to enhance mechanical properties and reduce production costs. Kaolin is added to rubber products, such as tires and conveyor belts, to RUBBER INDUSTRY improve their mechanical strength and abrasion resistance.

It is used in cosmetics and personal care products, including face masks, COSMETICS as a gentle exfoliant and thickening agent.

Kaolin is used in pharmaceutical formulations as an excipient, binder, PHARMACEUTICALS and anti-caking agent in tablets and capsules.

It is used in the formulation of agrochemicals, such as pesticides and AGROCHEMICALS herbicides, to improve dispersion and adhesion to plant surfaces.

In the production of fiberglass and reinforced plastics, kaolin is used to enhance the strength and durability of composite materials. REINFORCEMENT

Product Typical Characteristics

FIBER

allimineralsinternational.com

- Mineral Structure
- Particle Size and Distribution
- Brightness and Whiteness

- Moisture Content
- Cation Exchange Capacity (CEC)
- Color and Appearance
- Chemical Reactivity

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us ____

(855)208-2224

info@mallimineralsinternational.com





KAOLIN LUMPS

KAOLIN POWDER

MATERIAL FORM		GRADE	
KAOLIN	LUMPS	RAW	
KAOLIN	POWDER	#200, #300, #325	

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT
Color	slightly off White
Density	2.2 to 2.6 g/cm ^a
Melting Point	1,700 to 1,800 °C
Mohs hardness	2
Grain Size	submicron to several
	micrometers

PARAMETERS	PERCENTAGE VALUE
SiO2	45 %
Al ₂ O ₃	38 %
Fe ₂ O ₃	0.5 %
MgO	0.11 %
CaO	0.61 %
K ₂ O	0.50 %
TiO ₂	0.76 %
Na,O	0.45 %



Garnet Sand Vinera

Our in-house manufacturing facility processes of garnet sand in different mesh sizes as per our customer's needs. We have access to abundant natural resources of garnet sand to supply to our customers worldwide.

MMI Garnet Sand Applications

ABRASIVE BLASTING	Garnet sand is a widely-used abrasive for surface cleaning and prepa- ration, ideal for removing paint, rust, and contaminants.
WATERJET CUTTING	It plays a vital role in high-precision waterjet cutting machines, effecti- vely slicing through metals, stone, and other materials.
ABRASIVE POWDERS	Garnet is ground into fine powders for use in grinding wheels, sandpaper, and abrasive products, ensuring smooth finishes.
WATER FILTRATION	Garnet sand is used in water treatment to filter out impurities and suspended solids from drinking water and industrial processes.
SANDPAPER	Known for durability, garnet-based sandpaper is favored in woodwor- king and metalworking, delivering smooth finishes.
OIL AND GAS INDUSTRY	Garnet acts as a proppant in hydraulic fracturing, aiding in fracture maintenance during oil and gas extraction.
MANUFACTURING	Garnet is utilized in manufacturing processes, including glass produc- tion, for shaping and finishing products.
PAINT AND COATINGS	Its abrasive qualities enhance paints and coatings for textured or anti-slip surfaces.
CONSTRUCTION MATERIAL	Garnet is added to materials like concrete and asphalt for improved skid resistance and durability.

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us

(855)208-2224

info@mallimineralsinternational.com

1451 East 8th Street. Jacksonville, FL 32206

Product Typical Characteristics

allimineralsinternational.com

- Mineral Structure
 - Particle Size and Distribution

- Moisture Content
 - Purity and Impurities
 - Melting Point
 - Chemical Reactivity



MATERIAL	FORM	GRADE
GARNET	SAND	#30,#40,#50,#60, #80 AND ABOVE

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT
Bulk Density	2.34T/m3
Specific Gravity	4.1
Hardness	7.4
Melting point	1260°c
Shape of Natural Grain	Sharp Angular

GARNET 30/60 MESH CHEMICAL ANALYSIS

GARNET 20/40 MESH CHEMICAL ANALYSIS

PARAMETERS	PERCENTAGE VALUE	PARAMETERS	PERCENTAGE VALUE
SiO ₂	35%	SiO ₂	35%
Al ₂ O ₃	21%	Al ₂ O ₃	21%
Fe ₂ O ₃	2%	Fe ₂ O ₃	2%
MgO	6%	MnO	1%
CaO	2%	CaO	2%
TiO ₂	1%	TiO ₂	1%
FeO	30%	FeO	30%
MnO	1%	MnO	1%



Andalusite Mineral

Andalusite is a mineral known for its heat-resistant properties and pleochroism, used in refractories, ceramics, abrasives, and gemstone jewelry.

MMI Andalusite Applications

REFRACTORIES	Refractories: Used in furnace linings and high-temperature equipment due to its exceptional heat resistance.
CERAMICS	Ceramics: Enhances the strength and thermal shock resistance of ceramic products.
FOUNDRY	Foundry: Used in casting molds and cores due to its ability to withstand high temperatures.
ABRASIVES	Abrasives: Employed in grinding and cutting tools for its hardness and durability.
JEWELRY	Jewelry: Gem-quality andalusite is cut and used in jewelry for its unique color-changing properties.
HIGH-PERFORMANCE CERAMICS	High-Performance Ceramics: Used in aerospace and electronics industries for its exceptional properties.
OIL AND GAS INDUSTRY	Oil and Gas Industry: Utilized in equipment linings for high-temperature applications.
INSULATION	Insulation: Found in refractory bricks for thermal insulation.
MINERAL COLLECTING	Mineral Collecting: Prized by mineral enthusiasts for its distinctive crystal structure.

Product Typical Characteristics

mallimineralsinternational.com

- Crystal Structure
- Color Variations
- Hardness and Durability
- Heat Resistance
- Density

- Thermal Shock Resistand
- Refractory Propert
- Ceramic Enhancement
- Gemstone Quality
- Foundry Applications
- Abrasiveness

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us ____

(855)208-2224

info@mallimineralsinternational.com





ANDALUSITE RAW

ANDALUSITE POWDER

Chemical Analysis of Andalusite

	AI2O3	SiO2	Fe2O3	TiO2	CaO	MgO	Na2O	K20	L.O.I
Typical (%)	56.21	38.97	1.11	0.19	0.21	0.18	0.20	0.87	0.97
Guarantee (%)	≥56		≤ 1.2						
Grain Size Distribution of 3-5	i (mm) Produc	t							
	<2.8	2.	.8-4	4-	4.7	>	4.7		
Typical (%)	4.2		3.7		6.5		5.6		
Range (%)	<5	45	5-55	30)-40	5	-10		
Chemical Analysis o	f CHePA57: 1-3	3,0-1 mn	n & Mille	d Produ	t (Fine s	ize are	produce	from 1	-3 mm)
	AI2O3	SiO2	Fe2O3	TiO2	CaO	MgO	Na2O	K20	L.O.I
Typical (%)	58.6	38.65	0.67	0.11	0.06	0.08	0.07	0.34	0.59
Guarantee (%)	≥57		≤ 0.8						
CHePA57: 1-3 mm Grain Size Distribution (mm)									
	0-0.6	06	-1.4		1.4-2.3	6	2.36	-3.35	> 3.36
Typical (%)	6.5	3	3.9		43.2		10	6.4	0.0
Range (%)	5-10	20	0-35		35-45		10	-20	0
CHePA57: 0-1 mm Grain Size Distribution (mm)									
	0-0.15	0.1	5-0.3		0.3-0.5		0.	5-1	> 0.60
Typical (%)	23.0		6.6		22.3			4.7	3.4
Range (%)	20-30	15	5-25		20-30		30	-40	<5
CHePA 57: Milled Sizing (Mesh)									
Sizing (Micron)		2	200	3	25				
			75		45				
Product Size [D95 (Micron)]			75		45				
Specific Gravity (g/cm³) >	3.1								

Mullite Mineral

It is a refractory material with excellent thermal stability, often used in high-temperature applications such as kiln linings, ceramic production, and aerospace components.

•	•		•	MMI Mullite	
٠	•	•	•		
•	•	•	•	Applications	

REFRACTORIES	Mullite is a crucial component in refractory materials for lining high-temperature equipment like kilns and furnaces.
CERAMIC PRODUCTION	It enhances ceramics' heat resistance and mechanical strength, crucial for products like kiln furniture and crucibles.
AEROSPACE	Mullite's lightweight and high-temperature resistance make it valuable for aerospace components such as heat shields and rocket nozzles.
ELECTRONICS	Used in electronic substrates and insulators due to its thermal stability and electrical insulating properties.
FOUNDRY INDUSTRY	Mullite serves as a refractory material for casting molds and cores in foundry applications.
METALLURGY	It's used to line furnaces in metallurgical processes for the production of metals and alloys.
GLASS PRODUCTION	Mullite helps maintain high temperatures in glass manufacturing, preventing contamination of the glass melt.
SOLAR PANELS	It serves as a substrate material in solar panels, ensuring efficient energy conversion.
ENVIRONMENTAL FILTERS	Mullite is used in ceramic filters for pollution control due to its resistance to high temperatures and corrosive environments.

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium arade minerals that cater to the specific requirements of our valued customers.

Contact Us ____

(855)208-2224

info@mallimineralsinternational.com

1451 East 8th Street, Jacksonville, FL 32206

Product Typical Characteristics

- Crystal Structure
 - Color and Appearance
- Density
- Thermal Stability
- Heat Resistance
- Mechanical Strength
- Electrical Proper
- Thermal Insulation
- Abrasion Resistance
- Chemical inditions
 - Applications and Uses





MULLITE GRITS

MULLITE POWDER

MATERIAL	FORM	GRADE
MULLITE	GRITS	GRITS
MULLITE	POWDER	#200

PHYSICAL PROPERTIES RESULT

PROPERTIES RESULT	
Color	white or light gray
Density	2.2 to 2.5 g/cm³
telting Point 1,850 to 1,900°	
Mohs hardness 6 - 7	
Grain Size	Grits, #200

SPECIFICATIONS	For Grits	For Fines	Zirmu
SiO ₂	22-27	20-25	15-18
Al ₂ O ₃	73-77	75-80	46-48
Fe ₂ O ₃	1.00	1.00	0.15
ZrO ₂			32-35
CaO	-	- :	0.15
Na²O	-	-	0.20
TiO ₂	0.50	0.50	0.15
Specific Gravity	2.90-3.15	2.90-3.15	



<mark>Barite</mark> Mineral

Barite, a mineral composed of barium sulfate (BaSO4), has numerous applications across various industries due to its unique properties.

MMI Barite

.

OIL AND GAS DRILLING Oil and Gas Drilling: Barite is a crucial component in drilling mud used in oil and gas exploration. It helps control well pressure, lubricates the drilling bit, and prevents blowouts during drilling operations, ensuring safe and efficient extraction of hydrocarbons.

MEDICAL IMAGING Medical Imaging: Barium sulfate, derived from barite, is used as a contrast agent in X-ray and CT scans of the gastrointestinal tract. It enhances the visibility of internal structures during medical imaging procedures, aiding in the diagnosis of various health conditions.

CONSTRUCTION AND CONCRETE CONC

RADIATION SHIELDING Radiation Shielding: Barite is used in the construction of radiation shielding materials, such as leaded concrete, to protect against ionizing radiation. This application is critical in medical facilities and nuclear power plants.

PAINTS AND Paints and Coatings: Barite is used as a filler in paints and coatings to increase their density, opacity, and resistance to chemicals. It also contributes to the quality of the painted surface.

FOUNDRY CASTING Foundry Casting: Barite is employed as a mold-release compound in foundry casting processes, helping to separate castings from molds easily and efficiently, which is essential in metal casting operations.

Product Typical Characteristics

- Density
 Color
 - Crystal Structure
 - Hardness
 - Transparence

- Heat Resistance
- Electrical Propertie
- Chemical Inertness
- Particle Size Distribution
- Impuritie
- Fluorescence Properties

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us ____

(855)208-2224

info@mallimineralsinternational.com





BARITE RAW

BARITE POWDER

MATERIAL	FORM	GRADE
BARITE RAW	LUMPS	RAW
BARITE	POWDER	200 MESH & 325 MESH

DISCIPLINE	: CHEMICAL	
Test/Parameter	Result	Unit
Barlum sulphate (as BaSO4)	92.08	% (w/w)
Moisture	0.17	% (w/w)
Extractable Carbonate (as CO3)	1359	mg/kg
Cadmium (as Cd)	ND(DL: 0.5)	mg/kg
Mercury (as Hg)	ND(DL: 0.1)	mg/kg
Arsenic (as As)	5.2	mg/kg
Lead (as Pb)	5.3	mg/kg
Magnesium (as MgO)	0.094	% (w/w)
Zinc (as Zn)	6.9	mg/kg
Specific gravity	4.233	-
Cation Exchange Capacity(MB Value)	0.10	meq/100 g
Remark: ND: Not detected DL:	Detection limit	1mg/kg = 1 ppm



<mark>Silica Sand</mark> Mineral

Silica sand is a granular material primarily composed of quartz and is widely used in various industries for its unique properties.

MMI Silica Sand Applications

. .

GLASS PRODUCTION	Essential for clarity, strength, and heat resistance in glass.
FOUNDRY CASTING	Used for molds and cores in metal casting due to its high-temperature resistance.
CONSTRUCTION	Enhances strength and durability in concrete and mortar.
WATER FILTRATION	Removes impurities from drinking water and industrial processes.
SEMICONDUCTOR	Produces single-crystal silicon for computer chips.
PLAY SURFACES	Provides drainage and safety in sports fields and playgrounds.
OIL & GAS FRACKING	Acts as proppants to extract oil and natural gas.
CERAMICS & POTTERY	Withstands high temperatures in firing processes.
SANDBLASTING	Used as an abrasive material to remove surface contaminants.
GOLF COURSE BUNKERS	Fills sand bunkers for golf courses, ensuring a consistent playing surface.
MANUFACTURING GLASS BOTTLES	Silica sand is a critical component in the production of glass bottles and containers for the packaging industry.
HORTICULTURE	Silica sand is used as a component in potting mixtures and soil amend- ments to improve drainage and aeration in plant growth.

Product Typical Characteristics

mallimineralsinternational.com

- Chemical Composition
- Color and Appearance
- Purity and Impurities Moisture Content
- Particle Size and Grain Distribution
 Abrasion Resistance

 - Shape and Texture

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us

(855)208-2224

info@mallimineralsinternational.com



TS. MESH	I SIZE	AMOUNT R	ETAINED	Multiples	PRODUCTS	Specification
MICR	MESH	IN GRAMS	IN %			
1700	12	0		5	0	MOISTURE
850	20	0		12	0	AFS no. 62.21
600	30	0.34	3.08	20	6.8	CLAY
425	40	2.74		30	82.2	FINES
300	50	14.59		40	583.6	LOT
212	70	34.37		50	1718.5	
150	100	32.83	96.23	70	2298.1	
106	140	14.44		100	1444	
75	200	0.58	0.58	140	81.2	
53	270	0		200	0	
				270	0	
тот	AL	99.	89		6214.4	

PHYSICAL PROPERTIES RESULT

RESULT
white or colorless
2.65 to 2.67 g/cm³
1,710 °C
7
Fine sand to coarse
sand & even granules.

PARAMETERS	PERCENTAGE VALUE
SiO ₂	96.43%
Al ₂ O ₃	1.47%
Fe ₂ O ₃	0.12%
MgO	0.26 %
CaO	0.04%
K ₂ O	0.72%
Na ₂ O	0.28%
CI	0.017%
F	<0.001



Ball Clay

Highly plastic and fine-grained clay used in ceramics for its molding and firing properties, crucial in porcelain and fine china production.

•	•	•	•	MMI Ball Clay
•	•	•	•	
•		•	•	Applications

CERAMICS	Ball clay is a vital component in ceramics and pottery, offering excellent plasticity for shaping and molding.
SANITARYWARE	It provides impermeability and a smooth finish, making it ideal for manu- facturing toilets and sinks.
TILES & PORCELAIN	Enhances the strength, color, and finish of high-quality tiles and porce- lain products.
CASTING SLIPS	Crucial in creating intricate ceramic shapes using casting slips.
CERAMIC GLAZES	Improves texture, gloss, and firing characteristics in ceramic glazes.
CEMENT	Acts as a supplementary material, enhancing concrete workability and durability.
DRILLING MUD	Stabilizes boreholes and controls fluid loss in oil and gas drilling.
PAPER INDUSTRY	Enhances paper quality and printability as a filler.
PAINTS & COATINGS	Used for smoothness, texture, and color control in paints and coatings.
FERTILIZERS	Improves consistency and binding in fertilizer formulations.
PESTICIDES	Serves as a carrier for active ingredients in some pesticide formulations.
SEALANTS & ADHESIVES	Acts as a thickening and binding agent in various adhesive products.

۲

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us

(855)208-2224

info@mallimineralsinternational.com

1451 East 8th Street. Jacksonville, FL 32206

Product Typical Mineral Structure Characteristics

- Color and Appearance
- Firing Temperature

mineralsinternational.com





BALL CLAY LUMPS

BALL CLAY POWDER

MATERIAL	FORM	GRADE
BALL CLAY	LUMPS	RAW
BALL CLAY	POWDER	#200, #325

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT
Bulk Density (gm/cc)	1.30 - 1.50
Specific gravity	2 - 2.50
Liquid limit (%)	50 - 65
Plastic limit (%)	34 - 37
Atterberg No	14 - 25
Dry Linear shrinkage (%)	7 - 8.50
Water of Plasticity (%)	12 - 32

PARAMETERS	PERCI	INT/	AGE VALUE
SiO ₂	32%	-	54 %
Al ₂ O ₃	32%		40%
Fe ₂ O ₃	0.3 %	-	2%
MgO	1.5 %	(4)) (4)	3 %
CaO	1%	2	3%
TiO,	3%	-	6%



Sillimanite Mineral

High-temperature aluminum silicate mineral valued for its heat resistance, excellent thermal stability, and versatility in refractory applications and ceramics.

MMI Sillimanite Applications

CERAMICS	It is used as a filler and reinforcement material in ceramics and pottery production to enhance the strength and thermal shock resistance of ceramic products.
FOUNDRY INDUSTRY	Sillimanite-based materials are used as mold and core materials in the foundry industry to create intricate and heat-resistant castings.
ABRASIVES	Sillimanite is used in the manufacturing of abrasive products like grinding wheels and sandpapers due to its hardness and abrasive properties.
NSULATION	It is utilized in the production of high-temperature insulation materials for use in furnaces, ovens, and other industrial equipment.
	Sillimanite is used as a coating material for welding electrodes, improving the quality and strength of welded joints in high-temperature applications.
ELECTRICAL	It finds use as an electrical insulator in high-temperature and high- voltage applications.
DIL AND GAS NDUSTRY	Sillimanite-based materials are used in the oil and gas industry as proppants to keep fractures open in hydraulic fracturing ("fracking") operations.
METALLURGY	Sillimanite is employed in metallurgical processes as a source of aluminum and as a raw material for the production of specialty alloys.

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us ____

(855)208-2224

info@mallimineralsinternational.com

1451 East 8th Street, Jacksonville, FL 32206

www.mallimineralsinternational.com

- Product Typical Characteristics
- Minoral Structure
 - Color and Appearance
 - Hardness
 Heat Resistance
 - Particle Size and Distribution
- Density
- Thermal Expansio
- Moisture Content
- Binder Properties
- Impurities
- Applications and Uses





SILLIMANITE RAW

SILLIMANITE POWDER

MATERIAL	FORM	GRADE
SILLIMANITE	SAND	200 MESH
SILLIMANITE	SAND	325 MESH

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT	
Chemical formula	Al2SiO5	
Color	white, gray, brown,	
	green, or bluish-green.	
Mohs Hardness	36.5 to 7.5.	
Specific Gravity	3.23 to 3.27	
Refractive Index:	1.653 to 1.673	
Melting Point	1,550 to 1,750° Celsius	

PARAMETERS	PERCENTAGE VALUE
SiO ₂	36.1%
Al ₂ O ₃	60.3%
Fe ₂ O ₃	0.46%
CaO	0.46%
TiO,	0.14%



<mark>Ilmenite</mark> Mineral

 High-temperature aluminum silicate mineral valued for its heat resistance, excellent thermal stability, and versatility in refractory applications and ceramics.

MMI ilmenite Applications

8

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us ____

(855)208-2224

info@mallimineralsinternational.com

1451 East 8th Street, Jacksonville, FL 32206

Product Typical Characteristics

- Minoral Structure
- Color and Appearance
- Particle Size and Distribution
- Titanium Dioxide Content
- Impurities

- Density
- Melting Point
- Heat Resistance
- Hardness
 - Applications and Uses

w.mallimineralsinternational.com



MATERIAL	FORM	GRADE
ILMENITE	SAND	#200, #325

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT
Color:	black or dark brown
Density:	4.68 to 4.76 g/cm ³
Melting Point:	1,545 °C
Mohs hardness:	5-6
Grain Size:	Fine to Coarse crystals

Mag purity Test of Ilmenite

Total	100
Non-mag	0.01 %
Garnet	0.03 %
Ilmenite	99.96 %
MINERALS	ILMENITE

PARAMETERS	PERCENTAGE VALUE
TiO ₂	54.278 %
MgO	0.689%
Al ₂ O ₃	0.574%
SiO2	0.859 %
P2O5	0.031%
SO3	0.00%
CaO	0.299%
V2O5	0.387%
Cr2O3	0.156%
MnO	1.353%
Fe ₂ O ₃	37.234%
ZnO	0.034%
As2O3	0.00%
ZrO2	0.066%
Nb2O5	0.036%
SnO2	0.013%
CeO2	0.246%
РЬО	0.00%
Th	30 ppm
U	10 ppm



Zircon Sand Mineral

Naturally accurring mineral used in ceramics, refractories foundries, and electronics for its heat-resistant, high-density characteristics and its role as a source of zirconium.

MMI Zircon Sand

.

CERAMICS AND REFRACTORIES	Enhances heat resistance in ceramics and refractory products.
FOUNDRY CASTING	Forms precise, heat-resistant molds for metal casting.
ZIRCONIA PRODUCTION	Transformed into high-strength zirconia used in aerospace and medical implants.
CERAMIC GLAZES	Improves appearance and texture in ceramic glazes.
REFRACTORY COATINGS	Used in precision casting processes as a refractory coating.
CHEMICAL INDUSTRY	Provides zirconium compounds for catalysts and coatings.
CASTING CORES	Creates cores for casting intricate metal shapes.
CERAMIC FILTERS	Removes impurities from molten metals in metal casting.
ZIRCONIUM ALLOYS	Used in high-tech applications due to corrosion resistance.
JEWELRY	Gem-quality zircon is used in jewelry for its brilliance.
ELECTRONICS	Zirconium dioxide in electronic ceramics.
OIL AND GAS	Employed for corrosion resistance and stability.

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us ____

(855)208-2224

info@mallimineralsinternational.com

- Product Typical Characteristics
- Minoral Structure
 - Particle Size and Distribution
 - Color and Appearance
- Density
- Heat Resistance
- Purity and Impurities
- Zirconia Content
- Hardness
- Melting Point
- Chemical Reactivity
- Applications and Uses

ZIRCON SAND



MATERIAL	FORM	GRADE
ZIRCON	SAND	#200, #325

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT
Color	Reddish brown to white
Density	4.6 to 4.7 g/cm ³
Melting Point	2,550 °C
Mohs hardness	7.5
Grain Size	10-300 micrometers

PARAMETERS	PERCENTAGE VALUE
SiO ₂	32.7%
Al ₂ O ₃	0.77%
Fe ₂ O ₃	0.17%
ZrO ₂ + HfO ₂	65.04 %
Th	0.027%
TiO ₂	0.19%
U	0.034%





Reach Us

PHONE: (855)208-2224EMAIL: INFO@MALLIMINERALSINTERNATIONAL.COMOFFICE: 1451 EAST 8TH STREET, JACKSONVILLE, FL 32206WEBSITE: WWW.MALLIMINERALSINTERNATIONAL.COM





imina.

Naturally occurring mineral with hardness and heat resistance, derived from bauxite through refining processes, serves as a vital precursor for aluminum production.

MI Alumina

NINI AIUTIIIU	•	•		•	•	•	
Applications	•			•		:/ • :	
Alumina's high heat resistance makes it a	essentic	al for	linin	g fur	nac	es & l	kilns.

.

• .

ABRASIVES	Used in grinding wheels and sandpapers for metal and woodworking.
CERAMICS	Forms the backbone of ceramics, providing strength and durability.
ELECTRONICS	Used in semiconductor components and insulators due to its electrical properties.
CATALYSTS	Serves as a catalyst support in chemical processes.
POLISHING COMPOUNDS	Used in lens polishing and glass manufacturing.
FILLER MATERIAL	Enhances the strength and thermal properties of composites.
ARTIFICIAL GEMSTONES	Used to create synthetic gemstones like sapphires.
MEDICAL IMPLANTS	Biocompatible alumina is used in dental and orthopedic implants.
CUTTING TOOLS	Used in cutting inserts and drills for machining applications.
BALLISTIC ARMOR	Provides protection in bulletproof vests and vehicle armor.
HIGH-PURITY ALUMINA (HPA)	High-Purity Alumina (HPA): Used in LED lighting, lithium-ion batteries, and advanced ceramics.

Product Typical Characteristics

REFRACTORIES

allimineralsinternational.com

- Particle Size
- Grade Classification

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us

(855)208-2224

info@mallimineralsinternational.com







WHITE FUSED ALUMINA

MATERIAL	FORM	SIZE
ALUMINA	GRITS	0-1 MM
ALUMINA	GRITS	1−3 MM
ALUMINA	GRITS	3-5 MM
ALUMINA	POWDER	#200 MESH

PHYSICAL PROPERTIES RESULT

CHEMICAL ANALYSIS

0.034%

RESULT	PARAMETERS	PERCENTAGE VALUE
Reddish brown to white	SiO ₂	32.7%
4.6 to 4.7 g/cm ³	Al ₂ O ₃	0.77%
2,550 °C	Fe ₂ O ₃	0.17%
7.5	ZrO ₂ + HfO ₂	65.04 %
10-300 micrometers	Th	0.027%
- 25	TiO ₂	0.19%
	Reddish brown to white 4.6 to 4.7 g/cm³ 2,550 °C 7.5	Reddish brown to white SiO ₂ 4.6 to 4.7 g/cm³ Al ₂ O ₃ 2,550 °C Fe ₂ O ₃ 7.5 ZrO ₂ + HfO ₂ 10-300 micrometers Th

U



Bauxite Mineral

Bauxite is a naturally occurring mineral rich in aluminum oxides and hydroxides. It's the primary source for aluminum production and is prized for its high alumina content.

•	•	•	•	MMI Baux
•	-	•	•	
•		•	•	Applicatio

MMI Bauxite
Applications



ALUMINUM PRODUCTION	Primary source for extracting aluminum metal.
REFRACTORIES	Used in high-temperature environments, like furnaces.
ABRASIVES	Provides abrasive grit for sandpapers and grinding wheels.
CEMENT	Adds alumina to enhance cement's strength and durability.
PROPPANTS	Used in hydraulic fracturing (fracking) for oil and gas extraction.
CHEMICAL INDUSTRY	Source of aluminum chemicals for various applications.
CERAMICS	Used in the production of ceramic products, like tiles and dinnerware
MANUFACTURING	Used in the creation of automotive parts and aircraft components.
NON-FERROUS ALLOYS	Used in the production of non-iron alloys.
ENVIRONMENTAL	Utilized in water purification and soil remediation.

APPLICATIONS

Product Typical Characteristics

- Chemical Composition

- Alumina Content
- Particle Size & Distribution

- Applications and Uses

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Contact Us

(855)208-2224

info@mallimineralsinternational.com



MATERIAL	FORM	SIZE
BAUXITE	GRITS	0-1 MM
BAUXITE	GRITS	1-3 MM
BAUXITE	GRITS	3-5 MM
BAUXITE	POWDER	#200 MESH

CHEMICAL ANALYSIS

PARAMETERS	MMIB89	MMIB87	MMIB85	MMIB80	MMIB78
Al ₂ O ₃	89.5	87.8	85.9	80.15	79.1
Fe ₂ O ₃	1.5	1.6	1.7	1.6	1.6
Cao	0.3	0.5	0.4	0.5	0.4
TiO ₂	3.5	3.5	3.56	3.5	3.5
AP	4	6	6	6	7
BD (gm/css)	3.3	3.28	3.25	3.17	3.0

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT
Color	white and gray to reddish-brown
Density	2.2 to 2.6 g/cm ³
Melting Point	2,072 °C
Mohs hardness	+3
Grain Size	500 µm to 2,000 µm



Magnesia Mineral

It serves as a crucial component in refractories, construction materials, ceramics, and more, thanks to its heat resistance, electrical insulation, and pH-regulating abilities.

MMI Magnesia Applications

REFRACTORIES	Essential for furnace linings in steel, cement, and glass production. Impro- ves heat resistance and prolongs equipment life.
CEMENT AND CONSTRUCTION	Enhances cement formulations for better durability and resistance to harsh conditions. Used in specialty concrete mixes for construction projects.
METALLURGY	Crucial refractory material in metal smelting and casting operations. Withstands extreme temperatures and chemical reactions.
CHEMICAL INDUSTRY	Utilized in chemical processes, like magnesium salts production and catalysts. Facilitates chemical reactions and acts as a pH regulator.
ELECTRICAL INDUSTRY	An excellent electrical insulator, it's used in electrical components like heating elements and insulating materials. Ensures safety in electrical applications.
AGRICULTURE	Adjusts soil pH to improve nutrient uptake for crops. Corrects acidic soils and enhances agricultural productivity.
HEALTHCARE	An ingredient in antacids and laxatives to alleviate digestive discomfort. Balances stomach acidity and aids in bowel movements.
ENVIRONMENTAL REMEDIATION	Used in water treatment to neutralize acidity and remove heavy metals. Helps clean contaminated water sources and mitigate environmental damage.

About MMI

Our company stands out as a premier manufacturer and supplier of a wide range of minerals in the USA. With an unwavering commitment to excellence, we take great pride in offering an extensive selection of high-quality minerals, including mica, quartz, feldspar, vermiculite, rutile, garnet, barite, kaolin, and more. Our state-of-the-art facilities and deep expertise enable us to produce premium grade minerals that cater to the specific requirements of our valued customers.

Product Typical Characteristics

mallimineralsinternational.com

- Crystal Structure
- Color and Appearance

Chemical Composition

- Density
- Hardne
- Melting Point

- Purity and Impurities
- Particle Size & Distribution
- Refractory Properties
- Thermal Conductivity
- Electrical Conductivity
- Applications and Uses

Contact Us ____

(855)208-2224

info@mallimineralsinternational.com





FUSED MAGNESIA

DEAD BURNT MAGNESITE

MATERIAL	FORM	SIZE
MAGNESIA	GRITS	0-1 MM
MAGNESIA	GRITS	⊩3 MM
MAGNESIA	GRITS	3-6 MM
MAGNESIA	POWDER	#200 MESH

CHEMICAL ANALYSIS

PARAMETERS	FUSED MAGNESIA	DEAD BURNT MAGNESIT	DEAD BURNT MAGNESITE
Grade	(2:1) RATIO WITH HIGH CRYSTAL	GRADE 95	GRADE 90
MGO	97%	95%	90%
SIO	0.6%	2%	4.5%
Cao	1.2%	1.5%	2%
Fe ₂ O ₃	0.6%	12%	1.2%
LOI	0.2%	0.3%	0.33%
BD (gm/css)	3.49	3.20	3.15

PHYSICAL PROPERTIES RESULT

PROPERTIES	RESULT
Color	gray, yellow, or brown
Density	2.2 to 3.0 g/cm ³
Melting Point	2,800 °C
Mohs hardness	5.5 to 6.5
Grain Size	100 µm to 1,000 µm